



WMF 5000 S

Maximum output. In minimum space.

Preview

Market launch June 2015



The WMF 5000 S is the ground-breaking highlight of the New Generation Plattform.

Its heavy-duty brewer guarantee delivering a consistently high number of cups within astoundingly compact dimensions. Equipped with the new WMF Dynamic Milk System (optional), the WMF 5000 S offers a variety of consistencies for hot and cold milk foam, as well as hot and cold milk.



325 mm



590 mm



706 mm



WMF 5000 S with Cup&Cool

Compact design



Optionally available with either WMF Dynamic Milk or Easy Milk System



Steam Jet for preheating cups



Large, lockable and removable hoppers

Large MMI touch display

Brush-finished stainless steel side panels and top cover

Peak performance thanks to heavy-duty brewers

Optionally fitted with Auto Steam system

Technical data WMF 5000 S	Easy Milk		Dynamik Milk	
Recommended daily output / max. hourly output*	up to 250 cups			
Power Supply	3,0 kW / 230 V	6,6 kW / 400 V	3,0 kW / 230 V	6,6 kW / 400 V
Hourly output in accordance with DIN 18873-2*				
Espresso / 2 Espressi	144 / 220			
Café Crème / 2 Café Crème	112 / 136			
Cappuccino / 2 Cappuccino	144 / 220			
Total hot water output per hour	160 cups	180 cups	160 cups	180 cups
Energy loss per day in accordance with DIN 18873-2	1,55 kWh			
Hot milk drinks	✓			✓
Hot milk foam drinks	✓			✓
Cold milk drinks	✓			✓
Cold milk foam drinks		no		✓
Coffee bean hopper	right 1100 g, middle 550 g			
Chocolate or topping container	1200 g			
Outer dimensions (width / height / depth)	325 mm / 706** mm / 590 mm			
Water supply	fresh water supply 3/8", TW10			
Flow pressure	with fresh water supply at least 0,2 MPA (2,0 bar) at 2 liters			
Net weight	approx. 37 kg			
Continuous sound pressure level (LpA)***	< 70 dB (A)			

* The output depends on the cup size, the quality settings, the dispenser, the equipment and the nominal power rating. The recommended max. daily output is based on the relevant service concept. These average values are for your information only. - Let our trained WMF employees put together a coffee machine solution that is designed to meet your needs.

** Height measured with bean hopper, with lock but without key.

*** The A-rated sound pressure level LpA (slow) and LpA (impulse) at the operators' workplace lies below 70 dB (A) in every operating mode. If the carbonate hardness is 5° dKH or above, a WMF water filter must be used.

WMF AG Coffee Machines International
Eberhardstrasse · D-73312 Geislingen/Steige, Germany
Phone: + 49 73 31 258 482 · Fax: +49 73 31 258 792
gastro-export@wmf.de · www.wmf-coffeemachines.com

3273 # 63.8368.0391 Printed in Germany 03.15

All technical changes, typographical mistakes and errors reserved for the entire contents.

ClimatePartner[®]
klimaneutral

Druck | ID: 10482-1503-1009

